



A ADD YH-40 TO N/A BLOCK E *REC*
INC. E.O. 204 A 1671 9-17-57 *HC* *Malloch, Lvs*
B SEE E.O. 204 AA 2276 11-27-57 *to* *Wing* F.GREEN
C SEE E.O. 204 CB-798; CHG. N/A BLOCK
TO SHOW HU-1 & ADDED HU-1A 2-2-59 *large* F.GREEN



STEEL STAMP 'UST101333'
PER BPS FW4050. USE
3/16 IN. FIGURES



TOOL USAGE BLOCK

COLUMN	V2	V3	V4	V5	V6	V7	V8
PARAGRAPH	REMARKS	TOOL NUMBERS	OPERATION	PART NUMBER & NAME	OPERATION	PART NUMBER & NAME	OF ASSEMBLY NUMBER
(C)	I	T101333	REMOVE	204-040-144 BEARING	FROM	204-040-160 OR 204-040-305 SLEEVE ASSY	204-040-003
(C)	II	T101333	REMOVE	204-040-144 BEARING	FROM	204-040-160 OR 204-040-305 SLEEVE ASSY	204-040-206
(C)	III	T101333	REMOVE	204-040-144 BEARING	FROM	204-040-160 OR 204-040-305	204-040-207
(C)	IV	T101333	REMOVE	204-040-144 BEARING	FROM	204-040-161 OR 204-040-306 SLEEVE ASSY	204-040-208
(A)	V	T101333	REMOVE	204-040-407 BEARING	FROM	204-040-404 SLEEVE ASSY	204-040-004
(C)(B)	VI	T101333	REMOVE	204-040-407 BEARING	FROM	204-040-414 OR 204-040-419 SLEEVE ASSY	204-040-004

T101333

C

2. [HEAT TREAT TO 160,000 ~ 180,000 P.S.I TENSILE
STRENGTH, ROCKWELL RC 36-40.
I. BREAK SHARP CORNERS .015 ~ .032
NOTES:

204-040-208	HU-1A	REF	REF
204-040-207	HU-1A	REF	REF
SASH NO.	NEXT ASSY	USED ON	
	APPLICATION		

PROPRIETARY RIGHTS NOT

THIS DATA IS PROPRIETARY TO BELL HELICOPTER COMPANY.
DISCLOSURE, REPRODUCTION, OR USE OF THIS DATA FOR
ANY PURPOSE IS FORBIDDEN WITHOUT WRITTEN AUTHOR-
IZATION FROM BELL HELICOPTER COMPANY.

SHOP COPY
RELEASED FOR PROG
DATE: 1/29/10 INT: *Ken*
09-04-13 *JK*